



ELECTROMECHANICAL VIBRATING GRIZZLY SCREENS

VIBRATION SCALPING
SOLUTIONS

For all types of industries



METALLURGY



WASTE
INDUSTRIAL



MSW



SLAG



WOOD



PLASTICS



BULK



MINERALS



SINEX

— VIBRATING PROCESS —

THE ELECTROMECHANICAL VIBRATING GRIZZLY SCREENS



ROBUST AND ADAPTABLE

- Suitable for all industries.
- Primary screening for any type of products (mineral industry, recycling, etc.).
- Custom design.



FEATURES DIMENSIONS:

WIDTH

400 mm to 2000 mm

LENGTH

800 mm to 7500 mm

SCREENING SURFACES:

0.5 m² to 8 m²

Construction

- ▶ Open design.
- ▶ 1 to 3 screening levels.
- ▶ Finish : galvanized / painted.

Coatings

- ▶ Reinforced receiving area.
- ▶ Non-sticking or wear-resistant, on request

Scalping area

- ▶ Bar sections.
- ▶ Steel/PU grid.
- ▶ High-strength perforated steel sheet.

Motorization

- ▶ Unbalanced motors.
- ▶ Low maintenance.
- ▶ Frequency Inverter (optional)
- ▶ Brake relay (optional)

- Installation Set.**
- ▶ On ground level

